

Product datasheet

Specifications



APC Smart-UPS, Line Interactive, 750VA, Tower, 230V, 6x IEC C13 outlets, SmartSlot, AVR, LCD

SMT750I

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead Time Usually Ships within 2 Weeks

Main

Main Input Voltage 230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V
240 V

Rated Power In W 500 W

Rated Power In Va 750 VA

Input Connection Type IEC 320 C14

Output Connection Type 6 IEC 320 C13
2 IEC Jumpers

Cable Length 1.83 m

Number Of Cables 1

Battery Type Lead-acid battery

Provided Equipment USB cable
Documentation CD
Smart UPS signalling RS-232 cable

Batteries & Runtime

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Extended Runtime 0

Number Of Battery Filled Slots 0

Number Of Battery Free Slots 0

Battery Recharge Time 3 h

Number Of Battery Replacement Quantity 1

Battery Life 3...5 year(s)

Replacement Battery [RBC48](#)

Battery Charger Power	49 W rated
-----------------------	------------

General

Number Of Power Module Filled Slots	0
-------------------------------------	---

Number Of Power Module Free Slots	0
-----------------------------------	---

Redundant	No
-----------	----

Physical

Colour	Black
--------	-------

Height	15.75 cm
--------	----------

Width	13.8 cm
-------	---------

Depth	35.81 cm
-------	----------

Net Weight	13.18 kg
------------	----------

Mounting Location	Front
-------------------	-------

Mounting Preference	No preference
---------------------	---------------

Mounting Mode	Not rack-mountable
---------------	--------------------

Two Post Mountable	0
--------------------	---

Usb Compatible	Yes
----------------	-----

Input

Input Voltage Limits	151...302 V adjustable 160...280 V
----------------------	---------------------------------------

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

Output

Harmonic Distortion	Less than 5 % at full load
---------------------	----------------------------

Maximum Configurable Power In Va	750 VA
----------------------------------	--------

Maximum Configurable Power In W	500 W
---------------------------------	-------

Transfer Time	4 ms typical : 8 ms maximum
---------------	-----------------------------

Ups Type	Line interactive
----------	------------------

Wave Type	Sine wave
-----------	-----------

Output Frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
------------------	--

Conformance

Product Certifications	CE EAC RCM VDE
------------------------	-------------------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Environmental

Acoustic Level	40 dBA
----------------	--------

Heat Dissipation	90 Btu/h
Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...15240.00 m
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control Panel	Multifunction LCD status and control console
Emergency Power Off	Optional
Free Slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge Energy Rate	540 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	30.1 cm
Package 1 Width	27.8 cm
Package 1 Length	49.9 cm
Package 1 Weight	14.23 kg
Unit Type Of Package 2	PAL
Number Of Units In Package 2	32
Package 2 Height	130.6 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	464 kg
Sccl4	731304269069

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)
