

Product datasheet

Specifications



APC Rack PDU 9000 Switched, ZeroU, 32A, 230V, (21) C13 & (3) C19

APDU9953

Overview

Lead time Usually in Stock

Main

Main Input Voltage	200 V 208 V 230 V
PDU type	Switched
Input Connection Type	IEC 60309 32 A 2P + E
Number of rack unit	0U
Cable length	3.05 m
Number of cables	1
Communication port protocol	SNMP Redfish
Provided equipment	Installation guide Rack mounting brackets Safety guide

Batteries & Runtime

Communication network type 10/100/1000BASE-T

Physical

Colour	Black
Height	182.9 cm
Width	5.6 cm
Depth	4.6 cm
Net weight	7.34 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	No
Mounting position	Vertical

Input

Permissible voltage	220...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Product certifications	VDE EAC RCM
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3

Environmental

Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	204 cm
Package 1 Width	12.4 cm
Package 1 Length	16.5 cm
Package 1 Weight	9.95 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------

Recommended replacement(s)