

summary	
Delivery date	Usually available from stock
main information	
Main Input Voltage	230 V AC 1 phase 400 V AC 3 phases
Other Input Voltage	230V 220V 400V
Main Output Voltage	400 V 3 phase 230 V 1 phase
Other Output Voltage	230 V 400 V
Rated power [W]	10000W
Rated power [VA]	10000VA
Output connector type	Hardwire 5-Wire (3PH+N+G)
Number of rack units	3U
Battery Type	External battery system
Included equipment	Software CD Stabilization /wall mounting feet USB cable User manual RS-232 configuration cable
Battery and run time	
voltage	+/- 96 V
Automatic detection and scalable delay time	0
Battery charging voltage (watts)	3800 W rated
Universal	
Redundant	No
Physical parameters	
color	Black
high	13.1cm
width	43.8cm
depth	67.8cm
net weight	25kg
Installation type	Rack-mounted
USB compatible	Yes
enter	
Input voltage limit	110...300 V half load 176...300 V full load
Number of input connectors	1 Hardwired 5-Wire (3PH+N+G)
Network frequency	40...70 Hz auto-sensing
output	
bypass type	Internal bypass (automatic and manual)
Crest coefficient	3:1
Maximum configurable power in VA	10000VA
Maximum configurable power (watts)	10000W
topology	Double conversion online
Waveform type	Sine wave
power	95% (full load)
Output frequency (synchronized with main frequency)	50/60 Hz +/- 3 Hz synchronized with main frequency
conformity	
certified product	CE
Standards compliant	EN/IEC 62040-1 EN/IEC 62040-2
environment	
sound level	60 dBA
heat dissipation	1450 Btu/h
Working altitude	0...3000 m
operating temperature	0...40°C
Storage ambient temperature	-15...60 °C
Storage height	0...15000m
IP protection level	IP20
Relative humidity	0...95 % non-condensing
Storage relative humidity	0...95 % non-condensing
Communications and Management	
alarm	Alarm when on battery: distinctive low battery alarm: overload continuous tone alarm
free slot	1
Alarm function	Multifunctional LCD status management console.
Surge protection and filtering	
Surge suppression energy	600 J
packaging unit	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25cm
Package 1 Width	58 cm
Package 1 Length	87 cm
Package 1 Weight	31.25kg
Contract warranty	
Warranty	2 years repair or replace