

summary

delivery date	Usually available from stock
----------------------	------------------------------

main information

Number of rack units	2U
-----------------------------	----

Battery Type	Lead-acid batteries
---------------------	---------------------

equipment provided	DC cable rack mount bracket user manual
---------------------------	---

Battery and Runtime

installation method	Rack mount
----------------------------	------------

pre-installed battery	0
------------------------------	---

empty battery slot	0
---------------------------	---

voltage	192V
----------------	------

physical parameters

color	Black
--------------	-------

high	8.8cm
-------------	-------

width	43.8 cm
--------------	---------

depth	68.5 cm
--------------	---------

product weight	53kg
-----------------------	------

installation type	Rack-mounted with kit
--------------------------	-----------------------

environment

operating temperature	0...40°C
------------------------------	----------

Relative humidity	0...95 % non-condensing
--------------------------	-------------------------

working altitude	0...3000 m
-------------------------	------------

storage environment temperature	-15...45°C
--	------------

storage relative humidity	0...95 % non-condensing
----------------------------------	-------------------------

storage height	0...15000m
-----------------------	------------

packaging unit

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	24.5cm
-------------------------	--------

Package 1 Width	83.6 cm
------------------------	---------

Package 1 Length	56.5 cm
-------------------------	---------

Package 1 Weight	59kg
-------------------------	------

SCC14	10731304346781
--------------	----------------

contract warranty

Warranty	Repair or replace within 2 years
-----------------	----------------------------------

[show more specifications](#) 

resource performance

Take-back program available 