

summary	
delivery date	Usually available from stock
main information	
Main Input Voltage	220 volts
Other Input Voltage	230V 240V
Main Output Voltage	220V
Other Output Voltage	230V 240V
Rated power [W]	6000W
Rated power [VA]	6000VA
Output connector type	Hardwire 3-wire (HN + E) 1
Number of rack units	2U
Battery Type	External battery system
Attached equipment	Basic UPS Signaling RS-232 Cable Software CD 1 DC cable Rack Mounting Bracket User Manual USB Cable
Battery and Runtime	
Other parameters	Can be set to 220, 230 or 240 output voltage
voltage	240V
pre-installed battery	0
empty battery slot	0
Battery Charging Voltage (Watts)	1170 W rated
universal	
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
physical parameters	
color	Black
high	8.8cm
width	43.8 cm
depth	61.5 cm
product weight	14kg
Mounting preference	No preference
installation type	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
enter	
Input voltage limit	110...300 V half load 176...300 V full load
Number of input connectors	1 hard wire 3-wire (1PH+N+G)
Network frequency	40...70 Hz auto-sensing
output	
bypass type	Internal bypass (automatic or manual)
crest factor	3:1
Maximum configurable power in VA	6000VA
Maximum Configurable Power (Watts)	6000W
topology	Double conversion connection
Waveform type	Sine wave
power	94 % (full load)
Output frequency (synchronized with main frequency)	50/60 Hz +/- 3 Hz synchronized to master frequency
compliance	
certified product	CE
environment	
sound level	55 dBA
working altitude	0...3000 m
operating temperature	0...40°C
storage environment temperature	-15...60°C
storage height	0...15000m
IP protection class	IP20
Relative humidity	0...95 % non-condensing
storage relative humidity	0...95 % non-condensing
Communications and Management	
alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
emergency shutdown	Yes
free slot	1
control Panel	Multifunctional LCD status management console.
Surge protection and filtering	
Surge suppression energy	600J
packaging unit	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24cm
Package 1 Width	76cm
Package 1 Length	60cm
Package 1 Weight	18kg
SCC14	10731304346651
contract warranty	
Warranty	Repair or replace within 2 years
<a href="#">show more specifications</a> 	