| summary | |
|---------------------------------|---|
| delivery date | Usually available from stock |
| main information | |
| product type | Replacement battery cartridge |
| Number of cables | 1 |
| Battery Type | Lead-acid batteries |
| equipment provided | All Connectors Needed |
| | Battery Recycling Guide Metal Battery Bay or Battery Cabinet |
| | Reusable Packaging Installation Guide |
| Battery and Runtime | |
| empty battery slot | 0 |
| pre-installed battery | 0 |
| installation method | Additional battery holder |
| voltage | 48V |
| RBC™ Quantity | 1 |
| Venturi Pipe | |
| physical parameters | |
| high | 7.6cm |
| width | 21.6 cm |
| depth | 53.3 cm |
| product weight | 19.09kg |
| installation type | Not rack-mountable |
| USB compatible | No |
| environment | |
| operating temperature | 040°C |
| working altitude | 010000ft |
| Relative humidity | 095 % |
| storage environment temperature | -1545°C |
| storage height | 0.0015240.00 m |
| storage relative humidity | 095 % |
| packaging unit | |
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 22.900 cm |
| Package 1 Width | 76.800 cm |
| Package 1 Length | 39.400 cm |
| Package 1 Weight | 20.450kg |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 80.000 cm |
| Package 2 Width | 80.000 cm |
| Package 2 Length | 120.000 cm |
| Package 2 Weight | 257.160kg |
| contract warranty | |
| Warranty | 2-year repair or replacement service, 30 days (Japan only) |
| | show more specifications A |
| | show more specifications / |