

Product datasheet

Specifications



APC Symmetra LX 12kVA scalable to 16kVA N+1 Tower, 220/230/240V or 380/400/415V

SYA12K16I

Overview

Presentation	High performance, redundant power protection with scalable power and runtime for space-constrained server rooms, and voice and data networks.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V 400 V 3 phases
Other Input Voltage	220 V 240 V 380 V 415 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	8400 W
Rated power in VA	12000 VA
Output connector type	Hard wire 3-wire (H N + E) 1
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD Installation guide User manual Web/SNMP management card

Batteries & Runtime

Number of battery filled slots	3
Number of battery free slots	1
Battery recharge time	3 h
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery charger power	861 W rated
Battery power in VAh	2592 VAh runtime
Battery life	3...5 year(s)
Replacement battery	SYBT5
Battery option	SYBT5 1 3456 VAh SYAXR9B9I 1 10368 VAh SYAXR9B9I 2 18144 VAh SYAXR9B9I 3 25920 VAh

SYAXR9B9I 4 33696 VAh
SYAXR9B9I 5 41472 VAh
SYAXR9B9I 6 49248 VAh
SYAXR9B9I 7 57024 VAh

Extended runtime	1
------------------	---

General

Product web sub-family	4kVA power increments
------------------------	-----------------------

Number of power module free slots	2
-----------------------------------	---

Number of power module filled slots	3
-------------------------------------	---

Redundant	Yes
-----------	-----

Physical

Colour	Black Silver
--------	-----------------

Height	93.7 cm
--------	---------

Width	48.3 cm
-------	---------

Depth	72.6 cm
-------	---------

Net weight	263.64 kg
------------	-----------

Mounting location	Front
-------------------	-------

Mounting preference	No preference
---------------------	---------------

Mounting mode	Not rack-mountable
---------------	--------------------

Two post mountable	0
--------------------	---

USB compatible	No
----------------	----

Input

Network frequency	45...65 Hz auto-sensing
-------------------	-------------------------

Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
----------------------------	--

Input voltage limits	155...276 V 290...480 V 3:1
----------------------	--------------------------------

Input harmonic distortion	Less than 7 % for full load
---------------------------	-----------------------------

Input Power Factor at Full Load	0.98
---------------------------------	------

Output

Maximum configurable power in W	11200 W
---------------------------------	---------

Harmonic distortion	Less than 5 % at full load
---------------------	----------------------------

Output frequency	47...63 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
------------------	--

Crest factor	Up to 5 : 1
--------------	-------------

UPS type	Double conversion online
----------	--------------------------

Wave type	Sine wave
-----------	-----------

Bypass type	Internal bypass (automatic and manual)
-------------	--

Maximum output current	55 A
------------------------	------

Maximum configurable power in VA	16000 VA
----------------------------------	----------

Conformance

Product certifications	C-Tick CE GOST VDE
Standards	EN 50091-1 EN 50091-2 EN 55022 class A EN 55024 EN 60950 IEC 60950

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...4572.00 m
Acoustic level	62 dBA
Heat dissipation	3707 Btu/h

Communications & Management

Free slots	1
Preinstalled device	Network management card 2 with environmental monitoring
Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	118.1 cm
Package 1 Width	59.9 cm
Package 1 Length	99.7 cm
Package 1 Weight	287.27 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)