

# Eaton 9PX2200IRT3U

Catalog Number: 9PX2200IRT3U

Eaton 9PX UPS, 2200 VA, 2200 W, Input: C20, Outputs: (8) C13, (2) C19, Rack/tower, 3U



## General specifications

Product Name	Catalog Number
Eaton 9PX UPS	9PX2200IRT3U
UPC	Product Length/Depth
743172081377	48.5 cm
Product Height	Product Width
13 cm	44 cm
Product Weight	Compliances
24.52 kg	CE Marked
	TUV
	cULus Listed
	CSA 22.2
	FCC part 15 Class B
	CISPR22 Class B

## Certifications

cULus Listed  
EAC  
CE  
ENERGY STAR certified  
IEC/EN 62040-1  
UL 1778  
IEC/EN 62040-2

## Battery

### Battery type

Sealed, lead-acid

### Runtime graph

[View runtime graph](#)

### Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

### Battery quantity

6

### Battery management

ABM & Temperature  
compensated charging  
method (user selectable)  
Automatic battery test  
Deep discharge protection  
Automatic recognition of  
external battery units

### Battery rating

12 V / 7 Ah

### Extended battery capability

Yes

## Electrical output

### Receptacle

(8) C13, (2) C19

### Voltage

230V

### Wattage

2200 W

### Output power factor

1

### Output voltage range

200/208/220/230/240 V +/- 1%

### Output waveform

Sine wave

### Output nominal voltage

230V default (200/208/220/230/240V)

### Voltage distortion output (linear load) - max

3

### Feed type

1

### Topology

Online/Double-conversion

### VA rating

2200 VA

## Electrical input

### Input connection

C20 4

### Input nominal voltage

230V default (200/208/220/230/240V)

### Nominal frequency

50/60 Hz

### Input power factor

>.99

### Input cord length

1.8m

## Communications

### Includes network card

No

### Communication

USB port (HID compliant)

Serial port (RS232)

Mini terminal block for  
remote On/Off

Mini-terminal block for  
remote power off

Mini-terminal block for  
output relay

Dry contacts (3 outputs, 1

#### Input voltage range

176-276 V (100-276 V with derating)

#### Input frequency range

40-70 Hz

input, optocoupler, DB9)

#### Ethernet interface

No

#### User interface

Multilingual graphical LCD display

#### Potential free switch contact

Yes

#### Expansion slots

One slot for optional communication card

#### Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

#### Type of interface

Other

### Environmental

#### Altitude

3000 m

#### Noise level

<40 dB at 1 meter

#### Temperature range

0° to 40°C (32° to 104°F)

#### Relative humidity

0-96% non-condensing

### Additional specifications

#### Construction type

482.6 mm (19 inch) device

#### Package contents

UPS

Input cable

(2) IEC-IEC output cables

USB cable

Serial cable

(2) brackets for 19" mounting

(2) Rack-mounting kit

(2) Supports for tower mounting

Cable locking system

Safety instructions

Quickstart guide

#### Phase (output)

1

#### Internal bypass

Yes

#### Auto shutdown function

Yes

#### Color

Black/silver

Efficiency

93.5

Rack mounting kit

Yes

Phase (input)

1

Hot swap power

No

## Resources

### Brochures

[Eaton UPS Services Quick Guide 2021](#)

[Eaton UPS and battery services](#)

### Compliance information

[EU declaration of conformity Eaton 9PX UPS](#)

### Declarations of conformity

[eaton-9px-declaration-of-conformity-en-us.pdf](#)

### Manuals and user guides

[Eaton 9PX 1-3 kVA UPS and 9PX EBM 48V and 72V - Installation and user manual](#)

[Eaton Bypass Power Module \(BPM\) user guide](#)

[Eaton 9PX 1-3 kVA UPS - Quick Start Guide](#)

### Specifications and datasheets

[Eaton Specification Sheet - 9PX2200IRT3U](#)

### Technical data sheets

[Eaton 9PX 1000-3000W UPS - Datasheet](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](#)