

Product datasheet

Specifications



APC High Performance Battery Module for the Symmetra PX 250/500kW



SYBT9-B6

Overview

Lead Time Usually in Stock

Main

Battery Type VRLA
Provided Equipment Installation guide

Batteries & Runtime

Battery Location Internal battery
Number Of Battery Blocks Per String 6
Battery Life 3...5 year(s)
Device Mounting Enclosed battery cartridge
Battery Voltage 384 V
Battery Power In Vah 5184 VAh

Physical

Height 15.9 cm
Width 10.7 cm
Depth 70 cm
Net Weight 153 kg

Conformance

Product Certifications cUL listed
EUROBAT
UL listed
VDE

Environmental

Ambient Air Temperature For Operation 18...27 °C
Operating Altitude 0...3333 ft
Relative Humidity 0...95 %
Ambient Air Temperature For Storage -15...40 °C
Storage Altitude 0.00...15240.00 m
Storage Relative Humidity 0...95 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	18 cm
Package 1 Width	81 cm
Package 1 Length	64.8 cm
Package 1 Weight	160.91 kg

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)