

Product datasheet

Specifications



RACK PDU, BASIC, HALF HEIGHT, 100-240V/20A, 220-240V/16A, (14) C13

AP6003A

Overview

Lead time Usually in Stock

Main

Colour Black

Product or component type PDU

PDU type Basic

Provided equipment Installation guide
Safety guide

Complementary

Input Voltage 230 V

Height 52.3 cm

Width 5.6 cm

Output Voltage 100 V
120 V
200 V
208 V
230 V
240 V

Depth 4.7 cm

Net weight 1.88 kg

mounting location Side

Mounting preference Lower

Input Plug Type IEC 60320 C20

mounting mode Not rack-mountable

Rack units 0U

USB compatible No

Mounting position Vertical

[In] rated current 16 A

Permissible voltage 100...240 V

Max line current 20 A

Input current limits 20 A

Load capacity 3300 VA

Network frequency 50/60 Hz

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Outlet type and quantity	14 IEC 60320 C13
--------------------------	------------------

Environment

Product certifications	cUL listed UL listed
------------------------	-------------------------

Ambient air temperature for operation	0...50 °C
---------------------------------------	-----------

Relative humidity	5...95 %
-------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

ambient air temperature for storage	-15...65 °C
-------------------------------------	-------------

Storage Relative Humidity	5...95 %
---------------------------	----------

Storage altitude	0.0000000000...15240.0000000000 m
------------------	-----------------------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	61.2 cm
------------------	---------

Package 1 Width	10.7 cm
-----------------	---------

Package 1 Length	12.3 cm
------------------	---------

Package 1 Weight	2.55 kg
------------------	---------

SCC14	10731304327766
-------	----------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)




Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Lead Free

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant](#)
[EU RoHS Declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)
