# Product datasheet

Specifications

## APC Rack PDU 9000 Switched, ZeroU, 16A, 230V, (21) C13 & (3) C19, IEC309 Cord

APDU9959EU3

## Overview

| | |
|---|---|
| **Lead time** | Usually in Stock |

## Main

| | |
|---|---|
| **Colour** | Black |
| **product or component type** | PDU |
| **PDU type** | Switched |
| **Cord length** | 3.00 m |
| **Number of cables** | 1 |
| **provided equipment** | Installation guide<br>Locking input power cord<br>Rack mounting brackets<br>Safety guide |

## Complementary

| | |
|---|---|
| **Input Voltage** | 230 V |
| **Height** | 179.4 cm |
| **Width** | 5.5 cm |
| **Output Voltage** | 230 V |
| **Depth** | 4.6 cm |
| **net weight** | 5.61 kg |
| **mounting location** | Side |
| **Mounting preference** | No preference |
| **Input Plug Type** | IEC 60309 16 A 2P + E<br>IEC 60320 C20 |
| **mounting mode** | Not rack-mountable |
| **Rack units** | 0U |
| **USB compatible** | No |
| **Mounting position** | Vertical |
| **Communication port protocol** | SNMP<br>Redfish |
| **Permissible voltage** | 220…240 V |
| **Max line current** | 16 A |
| **Input current limits** | 16 A |
| **Load capacity** | 3700 VA |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Network frequency** | 50/60 Hz |
| **Outlet type and quantity** | 21 IEC 60320 C13<br>3 IEC 60320 C19 |
| **Communication network type** | 10/100/1000BASE-T |

## Environment

| | |
|---|---|
| **Product certifications** | FCC part 15 class A<br>VDE<br>RCM<br>EAC |
| **Standards** | EN 55022 class A<br>EN 55024<br>EN 61000-3-2<br>EN 61000-3-3<br>ICES-003 |
| **Ambient air temperature for operation** | -5…60 °C |
| **Relative humidity** | 5…95 % |
| **Operating altitude** | 0...10000 ft |
| **Ambient air temperature for storage** | -25…65 °C |
| **Storage Relative Humidity** | 5…95 % |
| **Storage altitude** | 0.0000000000…15240.0000000000 m |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 200.2 cm |
| **Package 1 Width** | 11.4 cm |
| **Package 1 Length** | 16.5 cm |
| **Package 1 Weight** | 8.59 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 3 years repair or replace |

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

Learn more about Green Premium >

Transparency

RoHS/REACh

## Well-being performance

| | |
|---|---|
| Mercury Free | |
| Rohs Exemption Information | Yes |

## Certifications & Standards

| | |
|---|---|
| **Reach Regulation** | REACh Declaration |
| **Eu Rohs Directive** | Compliant with Exemptions |
| **China Rohs Regulation** | China RoHS declaration |
| **Environmental Disclosure** | Product Environmental Profile |
| **Weee** | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| **Circularity Profile** | End of Life Information |