

# Maintenance Bypass Panel, single unit, 150kW 400V wallmount, for Galaxy VS and Easy UPS 3M

GVSBPSU150KH

#### Overview

Presentation	Maintenance bypass cabinet for complete isolation of the UPS during service operations.
Lead time	Usually Ships within 2 Weeks

#### Main

Main Input Voltage	400 V 3 phases	
Product or component type	Panel	
Range of product	Galaxy VS	
Range compatibility	Galaxy VS	

# **Physical**

Height	80 cm
Width	60 cm
Depth	28 cm
Net weight	48 kg

#### **Environmental**

Ambient air temperature for operation	040 °C	
Operating altitude	03000 ft	
Relative humidity	095 % non-condensing	
Ambient air temperature for storage	-2555 °C	
Storage Relative Humidity	095 % non-condensing	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	49 cm
Package 1 Width	84 cm
Package 1 Length	122 cm
Package 1 Weight	60 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### 

Environmental Disclosure

Product Environmental Profile

#### **Use Better**

EU RoHS Directive	Compliant with Exemptions
SCIP Number	5aa5ed58-9f72-49f2-ad76-720ad4129c6e
REACh Regulation	REACh Declaration

#### Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins