



SEP6 PDU, Basic Type, 0U, 63A, 400V (12+12)GB1002, left side

SEP6161

overview

Delivery time Usually available in stock.

Key Information

color black

Product Type PDU

PDU type Basic

Cable quantity 1

The equipment provided Vertical mounting bracket

Additional Information

Input Voltage 400V AC 3-phase
380/400/415V

Output Voltage 230V

Installation location side

Installation preferences No preference

Installation type Rack-mounted

Rack units 0U

Installation location vertical

Voltage range 200...240 V

Load capacity 43470 AND

Number of sockets in a socket product 24

Network frequency 50/60 Hz

Outlet type and quantity 24 Chinese outlet chinese outlet

environment

Product Certification THIS

Operating temperature -5...60 °C

relative humidity 5...95 %

Working altitude 0...3000 m

Storage ambient temperature -25...65 °C

Storage relative humidity 5...95 %

Storage height 0...15000 m

Packaging unit

Packaging 1: Packaging Unit Type	PCE
Units/kg	1
Packaging 1: Height	201 cm
Package 1: Width	25 cm
Packaging 1: Length	15 cm
Packaging weight	9.3 kg

Contract Warranty

Warranty (months)	24
-------------------	----



Environmental Data

Schneider Electric aims to build supply chain partnerships, reduce the impact of materials, and promote material recycling through its ongoing "Use Better, Use Longer, Reuse" campaign.

The goal is to achieve net-zero emissions by 2050.

Environmental Data Description >

Environmental footprint	
Total carbon footprint over life cycle	5 737 kg CO2 eq.
Environmental Disclosure	Product Environment Documentation
Carbon footprint of the manufacturing stage [A1–A3]	93 kg CO2 eq.
Carbon footprint during the distribution phase [A4]	50 kg CO2 eq.
Carbon footprint during the installation phase [A5]	0.3 kg CO2 eq.
Carbon footprint during the usage phase [B2, B3, B4, B6]	5 579 kg CO2 eq.
Carbon footprint at the end of the life cycle [C1–C4]	15 kg CO2 eq.

Use Better

Materials and Packaging	
Recycled cardboard packaging	no
Plastic-free packaging	no
EU RoHS Directive	Eligible for exemption
REACH regulations	REACH Statement
China RoHS Management Measures	China RoHS Statement

Use Longer

Lifespan extension	
repair	No

Use Again

Repackaging and Remanufacturing	
Circulation materials	End-of-life information for products
Removable battery	no
Recycle	Not supported