



# SEP6 PDU, Basic Type, 1U, 16A, 230V (8)GB1002

SEP6110

overview

|               |                             |
|---------------|-----------------------------|
| Delivery time | Usually available in stock. |
|---------------|-----------------------------|

Key Information

|                |       |
|----------------|-------|
| color          | black |
| Product Type   | PDU   |
| PDU type       | Basic |
| Cable quantity | 1     |

Additional Information

|                                       |                                 |
|---------------------------------------|---------------------------------|
| Input Voltage                         | 200...240 V AC 1 phase          |
| Output Voltage                        | 200...240 V                     |
| Installation location                 | front                           |
| Installation preferences              | No preference                   |
| Installation type                     | Rack-mounted                    |
| Rack units                            | 1U                              |
| Installation location                 | Horizontal direction            |
| Voltage range                         | 200...240 V                     |
| Load capacity                         | 3680 VA                         |
| Number of sockets in a socket product | 8                               |
| Network frequency                     | 50/60 Hz                        |
| Outlet type and quantity              | 8 Chinese outlet chinese outlet |

environment

|                             |             |
|-----------------------------|-------------|
| Product Certification       | THIS        |
| Operating temperature       | -5...60 °C  |
| relative humidity           | 5...95 %    |
| Working altitude            | 0...3000 m  |
| Storage ambient temperature | -25...65 °C |
| Storage relative humidity   | 5...95 %    |
| Storage height              | 0...15000 m |

Packaging unit

|                                  |         |
|----------------------------------|---------|
| Packaging 1: Packaging Unit Type | PCE     |
| Units/kg                         | 1       |
| Packaging 1: Height              | 54 cm   |
| Package 1: Width                 | 15.4 cm |
| Package 1: Length                | 6.8 cm  |
| Packaging weight                 | 1.27 kg |

Contract Warranty

|                   |    |
|-------------------|----|
| Warranty (months) | 24 |
|-------------------|----|



## Environmental Data

Schneider Electric aims to build supply chain partnerships, reduce the impact of materials, and promote material recycling through its ongoing "Use Better, Use Longer, Reuse" campaign.

The goal is to achieve net-zero emissions by 2050.

Environmental Data Description >

| Environmental footprint                                  |                                                   |
|----------------------------------------------------------|---------------------------------------------------|
| Total carbon footprint over life cycle                   | 440 kg CO2 eq.                                    |
| Environmental Disclosure                                 | <a href="#">Product Environment Documentation</a> |
| Carbon footprint of the manufacturing stage [A1-A3]      | 13 kg CO2 eq.                                     |
| Carbon footprint during the distribution phase [A4]      | 7 kg CO2 eq.                                      |
| Carbon footprint during the installation phase [A5]      | 0 kg CO2 eq.                                      |
| Carbon footprint during the usage phase [B2, B3, B4, B6] | 418 kg CO2 eq.                                    |
| Carbon footprint at the end of the life cycle [C1-C4]    | 2 kg CO2 eq.                                      |

## Use Better

| Materials and Packaging           |                                      |
|-----------------------------------|--------------------------------------|
| Recycled cardboard packaging      | no                                   |
| Plastic-free packaging            | no                                   |
| <a href="#">EU RoHS Directive</a> | Eligible for exemption               |
| REACH regulations                 | <a href="#">REACH Statement</a>      |
| China RoHS Management Measures    | <a href="#">China RoHS Statement</a> |

## Use Longer

| Lifespan extension |    |
|--------------------|----|
| repair             | No |

## Use Again

| Repackaging and Remanufacturing |                                                      |
|---------------------------------|------------------------------------------------------|
| Circulation materials           | <a href="#">End-of-life information for products</a> |
| Removable battery               | no                                                   |
| Recycle                         | Not supported                                        |